

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	15	provid\$4 and restrict\$4 and transm\$6 and configerat\$4 adj file and maintain\$3 and TFTP and us\$3 and DHCP adj server and associate and un adj modified and CM configuration and filename and IP adj address and receipt and DHCP adj REQUEST and stor\$3 and coordination adj pass adj phrase and generat\$4 first adj authentication adj key and creat\$3 and modif\$5 combin\$3 and authentication adj key and transmit\$4 and DHCP adj RESPONSE and TFTP and server and pars\$3 and second adj authentication adj key and match\$3 and depend not adj known.clm.	US-PGPUB	OR	ON	2007/08/16 16:18
L2	411626	provid\$4 with restrict\$4 with transm\$6 with configerat\$4 adj file with maintain\$3 with TFTP with us\$3 with DHCP adj server with associate with un adj modified with CM configuration with filename with IP adj address with receipt with DHCP adj REQUEST with stor\$3 with coordination adj pass adj phrase with generat\$4 first adj authentication adj key with creat\$3 with modif\$5 combin\$3 with authentication adj key with transmit\$4 v DHCP adj RESPONSE with TFTP with server with pars\$3 with second adj authentication adj key with match\$3 with depend not adj known.clm.	US-PGPUB	OR	ON	2007/08/16 16:21
L3	134998	I2 and @py<"2004"	US-PGPUB	OR	ON	2007/08/16 16:30
L4	7414	713/200	US-PGPUB; USPAT	OR	ON	2007/08/16 16:30
L5	1	I1 and L4	US-PGPUB	OR	ON	2007/08/16 16:31
L6	305	726/4	US-PGPUB; USPAT	OR	ON	2007/08/16 16:31
L7	0	I1 and L6	US-PGPUB	OR	ON	2007/08/16 16:31
L8	80	726/18	US-PGPUB; USPAT	OR	ON	2007/08/16 16:31
L9	0	I1 and L8	US-PGPUB	OR	ON	2007/08/16 16:31

EAST Search History

L10	138	726/21	US-PGPUB; USPAT	OR	ON	2007/08/16 16:31
L11	0	I1 and L10	US-PGPUB	OR	ON	2007/08/16 16:32
L12	2961	713/168	US-PGPUB; USPAT	OR	ON	2007/08/16 16:32
L13	4	I1 and L12	US-PGPUB	OR	ON	2007/08/16 16:34
L14	159	380/229	US-PGPUB; USPAT	OR	ON	2007/08/16 16:34
L15	0	I1 and L14	US-PGPUB	OR	ON	2007/08/16 16:35
L16	783	705/67	US-PGPUB; USPAT	OR	ON	2007/08/16 16:35
L17	0	I1 and L16	US-PGPUB	OR	ON	2007/08/16 16:35
L18	174	I2 and L4	US-PGPUB	OR	ON	2007/08/16 16:36
L19	0	I2 and L6	US-PGPUB	OR	ON	2007/08/16 16:36
L20	0	I2 and L8	US-PGPUB	OR	ON	2007/08/16 16:36
L21	0	I2 and L10	US-PGPUB	OR	ON	2007/08/16 16:36
L22	123	I2 and L12	US-PGPUB	OR	ON	2007/08/16 16:37
L23	1	I2 and L14	US-PGPUB	OR	ON	2007/08/16 16:37
L24	11	I2 and L16	US-PGPUB	OR	ON	2007/08/16 16:37
S1	16	"6598057"	US-PGPUB; USPAT	OR	ON	2007/08/16 15:54
S2	1	10/613659	US-PGPUB; USPAT	OR	ON	2007/08/14 16:13
S3	81	first adj authentication adj key	US-PGPUB; USPAT	OR	ON	2007/08/14 16:13
S4	71	second adj authentication adj key	US-PGPUB; USPAT	OR	ON	2007/08/14 16:32
S5	61	S3 and S4	US-PGPUB; USPAT	OR	ON	2007/08/14 16:14
S6	7414	713/200	US-PGPUB; USPAT	OR	ON	2007/08/14 16:15
S7	5	S5 and S6	US-PGPUB; USPAT	OR	ON	2007/08/14 16:31
S8	6726	dhcp	US-PGPUB; USPAT	OR	ON	2007/08/14 16:31
S9	1395	tftp	US-PGPUB; USPAT	OR	ON	2007/08/14 16:31
S10	717	S8 and S9	US-PGPUB; USPAT	OR	ON	2007/08/14 16:31
S11	1	S10 and S5	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23

EAST Search History

S12	3887	authentication adj key	US-PGPUB; USPAT	OR	ON	2007/08/14 16:32
S13	9	S10 and S12	US-PGPUB; USPAT	OR	ON	2007/08/14 16:57
S14	747	dhcp adj request	US-PGPUB; USPAT	OR	ON	2007/08/14 16:58
S15	216	dhcp adj response	US-PGPUB; USPAT	OR	ON	2007/08/14 16:58
S16	6	S14 adj S15	US-PGPUB; USPAT	OR	ON	2007/08/15 08:28
S17	320	tftp adj server	US-PGPUB; USPAT	OR	ON	2007/08/14 17:09
S18	0	S16 and S17	US-PGPUB; USPAT	OR	ON	2007/08/14 17:09
S19	3323	dhcp adj server	US-PGPUB; USPAT	OR	ON	2007/08/14 17:10
S20	192	S17 and S19	US-PGPUB; USPAT	OR	ON	2007/08/14 17:10
S21	0	S20 and S16	US-PGPUB; USPAT	OR	ON	2007/08/14 17:11
S22	1	S20 and S5	US-PGPUB; USPAT	OR	ON	2007/08/14 17:11
S23	2	S20 and S12	US-PGPUB; USPAT	OR	ON	2007/08/14 17:16
S24	587283	match	US-PGPUB; USPAT	OR	ON	2007/08/14 17:16
S25	75	S24 and S20	US-PGPUB; USPAT	OR	ON	2007/08/14 17:16
S26	22	S25 and @py<"2004"	US-PGPUB; USPAT	OR	ON	2007/08/15 07:10
S27	1	09/470105	US-PGPUB; USPAT	OR	ON	2007/08/15 07:10
S28	1395	tftp	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23
S29	747	dhcp adj request	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23
S30	216	dhcp adj response	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23
S31	6	S29 adj S30	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23
S32	0	S28 and S31	US-PGPUB; USPAT	OR	ON	2007/08/15 08:23
S33	8	09/800803	US-PGPUB; USPAT	OR	ON	2007/08/15 08:35

EAST Search History

S34	4	09/018400	US-PGPUB; USPAT	OR	ON	2007/08/15 13:17
S35	61	"5870134"	US-PGPUB; USPAT	OR	ON	2007/08/15 17:17
S36	27	"5506905"	US-PGPUB; USPAT	OR	ON	2007/08/15 17:32
S37	8	09/800803	US-PGPUB; USPAT	OR	ON	2007/08/15 18:17
S38	304	726/4	US-PGPUB; USPAT	OR	ON	2007/08/15 18:17
S39	80	726/18	US-PGPUB; USPAT	OR	ON	2007/08/15 18:17
S40	138	726/21	US-PGPUB; USPAT	OR	ON	2007/08/15 18:17
S41	2954	713/168	US-PGPUB; USPAT	OR	ON	2007/08/15 18:18
S42	27	713/155-159	US-PGPUB; USPAT	OR	ON	2007/08/15 18:18
S43	158	380/229	US-PGPUB; USPAT	OR	ON	2007/08/15 18:18
S44	783	705/67	US-PGPUB; USPAT	OR	ON	2007/08/15 18:28
S45	0	coordination adj passphrase	US-PGPUB; USPAT	OR	ON	2007/08/15 18:29
S46	1	coordination adj pass adj phrase	US-PGPUB; USPAT	OR	ON	2007/08/15 18:29

10/69,K/6 (Item 6 from file: 350)
DIALOG(R)File 350:Derwent WPIX
(c) 2007 The Thomson Corporation. All rts. reserv.

0010262820 - Drawing available
WPI ACC NO: 2000-575421/200054
XRPX Acc No: N2000-42587.1

Asynchronous input-output cache memory has pair of circuits for accessing system data bus and input-output data bus respectively, based on data stored in data memory area

Patent Assignee: HEWLETT-PACKARD CO (HEWP); HEWLETT-PACKARD DEV CO LP (HEWP)

Inventor: MONISH; THOMAS; SHAH M S; SPENCER T V

Patent Family (2 patents, 2 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update
JP 2000227877	A	20000815	JP 1999360373	A	19991220	200054 B
US 7035981	B1	20060425	US 1998218333	A	19981222	200628 E

Priority Applications (no., kind, date): US 1998218333 A 19981222

Patent Details

Number	Kind	Lan	Pg	Dwg	Filing Notes
JP 2000227877	A	JA	10	4	

Alerting Abstract JP A

NOVELTY - The cache has data memory area (120) for communicating with system data bus and input-output data bus, simultaneously. Based on the data stored in memory area, a pair of circuits access input-output data bus and system bus, respectively.

USE - In e.g. asynchronous input-output cache memory.

ADVANTAGE - Queuing time in both system optical frequency domain and input-output frequency domain is reduced due to the presence of the pair of circuits.

DESCRIPTION OF DRAWINGS - The figure shows the block diagram of asynchronous input-output cache memory.

120 Data memory area

Title Terms/Index Terms/Additional Words: ASYNCHRONOUS; INPUT; OUTPUT; CACHE; MEMORY; PAIR; CIRCUIT; ACCESS; SYSTEM; DATA; BUS; RESPECTIVE; BASED; STORAGE; AREA

Class Codes

International Classification (Main): G06F-012/08

International Classification (+ Attributes)

IPC + Level Value Position Status Version

G06F-0013/00 A I F B 20060101

US Classification, Issued: 711144000, 711145000, 711141000, 711147000, 711167000, 711130000, 711162000, 709400000, 713400000, 713502000, 713600000, 710019000, 710027000, 710055000, 710061000, 710107000, 710125000, 710200000, 710240000, 710244000, 710305000

File Segment: EPI;

DWPI Class: T01

Manual Codes (EPI/S-X): T01-H05B2

Original Publication Data by Authority

Original Abstracts:

The present invention is generally directed to a device including an

asynchronous input/output (I/O) data cache. The device includes a single data storage area that is disposed in communication with both a system data bus and a I/O data bus. Similarly, the device includes an address storage area that is configured to store system addresses corresponding to data contemporaneously stored in the data storage area. The device further includes a first circuit configured to indicate validity status of data within the data storage area for immediate access from the I/O data bus. A similar, second circuit is also included and configured to indicate validity status of data within the data storage area for immediate access from the system data bus. In accordance...

...I/O data bus, and providing a single address storage area configured to store system memory addresses corresponding to data contemporaneously stored in the data storage area. In accordance with the broad aspect of the

...

Claims:

...communication with both a system data bus and an I/O data bus, wherein the data storage area is configured to store a non-duplicative data set; a single address storage area configured to store system addresses corresponding to data contemporaneously stored in the data storage area; a first circuit configured to indicate validity status of data within the data storage area for immediate access from the I/O data bus; and a second circuit configured to indicate validity status of data within the data storage area for immediate access from the system data bus, wherein the second circuit is configured such that the validity status of the data stored within the data storage area never appears valid from the I/O data bus, without first appearing valid from the system...

10/69,K/7 (Item 7 from file: 350)

DIALOG(R)File 350:Derwent WPIX

(c) 2007 The Thomson Corporation. All rts. reserv.

0009182557 - Drawing available

WPI ACC NO: 1999-106394/199909

XRPX Acc No: N1999-076789

Telecommunication system secure service connection - By encrypting data transmitted via secure connection using encrypting algorithm

Patent Assignee: SONERA OY (SONE-N); SONERA OYJ (SONE-N); TELECOM FINLAND OY (TELE-N); TELIASONERA FINLAND OYJ (TELI-N); SONERA SMARTTRUST OY (SONE-N)

Inventor: VATANEN H

Patent Family (12 patents, 81 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update
WO 1999001990	A2	19990114	WO 1998FI532	A	19980618	199909 B
FI 199702819	A	19981231	FI 19972819	A	19970630	199920 E
AU 199877717	A	19990125	AU 199877717	A	19980618	199923 E
EP 1027806	A2	20000816	EP 1998925695	A	19980618	200040 E
			WO 1998FI532	A	19980618	
US 6237093	B1	20010522	WO 1998FI532	A	19980618	200130 E
			US 1999474409	A	19991229	
AU 739814	B	20011018	AU 199877717	A	19980618	200174 E
NZ 502187	A	20011130	NZ 502187	A	19980618	200207 E
			WO 1998FI532	A	19980618	
JP 2002511994	W	20020416	WO 1998FI532	A	19980618	200242 E
			JP 1999506485	A	19980618	
EP 1027806	B1	20051123	EP 1998925695	A	19980618	200577 E
			WO 1998FI532	A	19980618	
DE 69832517	E	20051229	DE 69832517	A	19980618	200603 E
			EP 1998925695	A	19980618	
			WO 1998FI532	A	19980618	
DE 69832517	T2	20060727	DE 69832517	A	19980618	200649 E
			EP 1998925695	A	19980618	
			WO 1998FI532	A	19980618	
FI 117366	B1	20060915	FI 19972819	A	19970630	200662 E

Priority Applications (no., kind, date): FI 19972819 A 19970630

Patent Details

Number	Kind	Lan	Pg	Dwg	Filing Notes
WO 1999001990	A2	EN	11	1	
National Designated States,Original: AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GE GH GM GW HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG US UZ VN YU ZW					
Regional Designated States,Original: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW NL OA PT SD SE SZ UG ZW					
AU 199877717	A	EN			Based on OPI patent WO 1999001990
EP 1027806	A2	EN			PCT Application WO 1998FI532
					Based on OPI patent WO 1999001990
Regional Designated States,Original: AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC NL PT SE					
US 6237093	B1	EN			Continuation of application WO 1998FI532
AU 739814	B	EN			Previously issued patent AU 9877717
					Based on OPI patent WO 1999001990
NZ 502187	A	EN			PCT Application WO 1998FI532
					Based on OPI patent WO 1999001990

JP 2002511994	W	JA	14	PCT Application WO 1998FI532
				Based on OPI patent WO 1999001990
EP 1027806	B1	EN		PCT Application WO 1998FI532
				Based on OPI patent WO 1999001990
Regional Designated States, Original:				AT BE CH CY DE DK ES FI FR GB GR IE
IT LI LT LU LV MC NL PT SE				
DE 69832517	E	DE		Application EP 1998925695
				PCT Application WO 1998FI532
				Based on OPI patent EP 1027806
				Based on OPI patent WO 1999001990
DE 69832517	T2	DE		Application EP 1998925695
				PCT Application WO 1998FI532
				Based on OPI patent EP 1027806
				Based on OPI patent WO 1999001990
FI 117366	B1	FI		Previously issued patent FI 9702819

Alerting Abstract WO A2

Method is for a system with telecommunication networks (1,3), terminal devices (2,4) and telecommunication server (5). Device (1) is connected via telecommunication connection (6) to the telecommunication server (5) and device (3) is connected to the server (5) via second telecommunication connection (7). The unique **address** of **device** (2) and the **data** needed for **verification** of information giving **device** (2) **access** to server (5) services are transmitted via **device** (4). The **data** sent by **device** (4) is verified and connection (6) is set up based on the **verification** and **address data** received if **device** (2) has the required right of access to the server services.

USE - Method is for setting up a secure service connection in a telecommunication system e.g. the Internet and a telephone network or mobile communication network.

ADVANTAGE - Method allows reliable user identification and allows him to order services offered by the network.

Title Terms/Index Terms/Additional Words: TELECOMMUNICATION; SYSTEM; SECURE ; SERVICE; CONNECT; DATA; TRANSMIT; ALGORITHM

Class Codes

International Classification (Main): H04M-011/00, H04Q-001/00
(Additional/Secondary): H04L-012/66, H04Q-007/22, H04Q-007/24, H04Q-007/26 , H04Q-007/30, H04Q-007/38

International Classification (+ Attributes)

IPC + Level Value Position Status Version

H04L-0029/06	A	I		R	20060101
H04Q-0001/00	A	I	F	B	20060101
H04L-0012/22	A	I	F		20060101
H04M-0011/00	A	I	L		20060101
H04L-0029/06	C	I		R	20060101

US Classification, Issued: 713168000, 713182000, 380255000, 713162000

File Segment: EPI;

DWPI Class: T01; W01

Manual Codes (EPI/S-X): T01-H07C5S; T01-J08C; W01-A05B; W01-C02B6A; W01-C05B3B

Alerting Abstract ...device (3) is connected to the server (5) via second telecommunication connection (7). The unique **address** of **device** (2) and the **data** needed for **verification** of information giving **device** (2) **access** to server (5) services are transmitted via **device** (4). The **data** sent by **device** (4) is verified and connection (6) is set up based on the

verification and address data received if device (2) has the required right of access to the server services...

Original Publication Data by Authority

Original Abstracts:

...telecommunication connection (7). In an embodiment of the invention, the unique address of the first **terminal device (2)** and the **data** needed for the **verification** of information giving **the first terminal device (2) access** to the **services** of the telecommunication server (5) are transmitted via the second terminal device (4); the data sent by the **second terminal device** are **verified** in the telecommunication server ; and the **first telecommunication connection (6)** from the telecommunication server to the first terminal device is **set up based** on the **verification** and the address **data** received if **the first terminal device** has the required right of access to the services of the telecommunication server...

...terminal device is connected to the telecommunication server via a second telecommunication connection. The unique **identifying** address of the **first terminal device** and the **data** needed to **verify** that the **first terminal device** is permitted **access** to the services of the telecommunication server are transmitted to the telecommunication server via the second terminal device and second telecommunication connection, and the **data** sent by the **second terminal device** are **verified** at the telecommunication server. If the **first terminal device** is determined to have the required right of access to the services of the telecommunication server, the first telecommunication connection from the telecommunication server to the first terminal device is **set up based** on the successful **verification** and using the address data received by the telecommunication server...

...connection (7). In an embodiment of the invention, the unique address of the first terminal **device (2)** and the **data** needed for the **verification of information** giving the **first terminal device (2) access** to the services of the telecommunication server (5) are transmitted via the second terminal **device (4)**; the **data** sent by the **second terminal device** are **verified** in the telecommunication server; and the **first telecommunication connection (6)** from the telecommunication server to the first terminal device is set up **based** on the **verification** and the address **data** received if the **first terminal device** has the **required** right of access to the services of the telecommunication server...

Claims:

...encrypted message packets;

transmitting via the second terminal device (4) the unique address of the **first terminal device (2)** and **information authorizing** the use of services and/or ordering of services to the telecommunication **server (5)**;

verifying the **data** sent by the **second terminal device (4)** in the telecommunication **server (5)**; and

setting up the first telecommunication connection (6) from the telecommunication server to the **first terminal device (2)** based on the **verification** and the **address data** received if the first terminal device (2) has the required right of access to use and/or order the services of the **telecommunication server (5)**.

...**5**), via the second terminal device (**4**) and the second telecommunication connection (**7**), a unique **identifying** address of

the first terminal device0 (2) and data permitting verification by the telecommunication server as to whether the first terminal device (2) is permitted access to a service provided by the telecommunication server (5); verifying, at the telecommunication server (5), the data sent to the telecommunication server via the second terminal device (4) and the second telecommunication...

...device (2) is permitted access to the service provided by the telecommunication server; and establishing, where said verifying step determines that the first terminal device (2) is permitted access to the service, the first telecommunication connection (6) between the first terminal device (3) and the telecommunication server (5) using the unique identifying address of the first terminal device (2) received by the telecommunication server (5) from the second terminal device.>

10/69,K/4 (Item 4 from file: 350)
DIALOG(R)File 350:Derwent WPIX
(c) 2007 The Thomson Corporation. All rts. reserv.

0014763117 - Drawing available
WPI ACC NO: 2005-110771/200512
XRPX Acc No: N2005-095681

Cable modem transmission restriction method for use with e.g. personal computer, involves transmitting configuration file to cable modem only if authentication keys generated based on configuration file match with each other

Patent Assignee: DANFORTH A (DANF-I); GOULD K (GOUL-I); TIME WARNER CABLE INC (TIME-N)

Inventor: DANFORTH A; GOULD K

Patent Family (2 patents, 2 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update
US 20050005154	A1	20050106	US 2003613659	A	20030703	200512 B
CA 2473326	A1	20060108	CA 2473326	A	20040708	200612 NCE

Priority Applications (no., kind, date): CA 2473326 A 20040708; US 2003613659 A 20030703

Patent Details

Number	Kind	Lan	Pg	Dwg	Filing Notes
US 20050005154	A1	EN	22	9	
CA 2473326	A1	EN			

Alerting Abstract US A1

NOVELTY - An unmodified cable modem (CM) configuration filename is associated to a CM internet protocol (IP) address and an authentication key is generated. A modified CM configuration filename is generated by combining previous filename with the key. The modified filename is parsed to unmodified filename by which a new authentication key is generated. The configuration file is transmitted to CM only when the keys match mutually.

USE - For providing restricted transmission of cable modem (CM) configuration file maintained on trivial file transfer protocol (TFTP) server, for use with terminal such as personal computer and game console device.

ADVANTAGE - Unauthorized access to CM configuration files is reduced or eliminated.

DESCRIPTION OF DRAWINGS - The figure illustrates CM request and response for establishing IP connectivity.

Technology Focus

INDUSTRIAL STANDARDS - The authentication key is generated by encryption functions specified by data encryption standard (DES), data encryption algorithm (DEA), extended data encryption standard (DESX), advanced encryption standard (AES) including Rivest's Cipher (RC6), digital signature algorithm (DSA), RC2, RC4, RC5, secure hash algorithm (SHA), message digest algorithm (MD2,MD4,MD5), international data encryption algorithm (IDEA), secure and fast encryption routine (SAFER), fast data encipherment algorithm (FEAL), Skipjack, Blowfish, Carlisle Adams and Stafford Travares (CAST) and ElGamal. The encrypted wireless network conforms to ~IEEE 802.11~ .

Title Terms/Index Terms/Additional Words: CABLE; MODEM; TRANSMISSION; RESTRICT; METHOD; PERSON; COMPUTER; TRANSMIT; CONFIGURATION; FILE; AUTHENTICITY; KEY; GENERATE; BASED; MATCH

Class Codes

International Classification (Main): H04L-009/00

International Classification (+ Attributes)

IPC + Level Value Position Status Version

H04L-0009/32 A I F 20060101

US Classification, Issued: 713200000

File Segment: EPI;

DWPI Class: T01; W01

Manual Codes (EPI/S-X): T01-C03A; T01-D01; T01-F05B2; W01-A05A

Cable modem transmission restriction method for use with e.g. personal computer, involves transmitting configuration file to cable modem only if authentication keys generated based on configuration file match with each other

Original Titles:

Method to block unauthorized access to TFTP server configuration files

Alerting Abstract ...NOVELTY - An unmodified cable modem (CM) configuration filename is associated to a CM internet protocol (IP) address and an authentication key is generated. A modified CM configuration filename is generated by combining previous filename with the key. The modified filename is parsed to unmodified filename by which a new authentication key is generated. The configuration file is transmitted to CM only when the keys match mutually. USE - For providing restricted transmission of cable modem (CM) configuration file maintained on trivial file transfer protocol (TFTP) server, for use with terminal such as personal...
...ADVANTAGE - Unauthorized access to CM configuration files is reduced or eliminated...

Original Publication Data by Authority

Original Abstracts:

The present invention teaches methods and systems for blocking unauthorized access to cable modem configuration files stored on trivial file transfer protocol (TFTP) servers. Filenames are modified by the DHCP to incorporate an authentication key (and optional cloaking) prior to transmission to the cable modem. When the TFTP server receives a modified filename, it also generates an authentication key. The authentication keys must match in order for the cable modem to receive the configuration file requested. At a minimum, authentication keys depend upon the un-modified filename, the cable modem IP address and a "coordination pass phrase" known to the TFTP server and DHCP server, but not known to the cable modem. Variations include optional cloaking, various actions performed for non-matching authentication keys, selection of authentication key generating algorithm and inclusion of cable modem MAC address in the authentication key for all cable modems or for premium service customer cable modems. >

Claims:

What is claimed is: 1. A method for providing restricted transmissions of cable modem (CM) configuration files maintained on a trivial file transfer protocol server (TFTP), the method comprising: using a dynamic host configuration protocol (DHCP) server to associate an un-modified CM configuration filename to a cable modem Internet protocol (IP) address upon receipt of a DHCP REQUEST;

storing a coordination pass phrase on a DHCP server and a TFTP server;generating a first authentication key ;creating a modified CM configuration filename by combining a CM configuration filename with the authentication key ;transmitting the modified CM configuration filename to the cable modem in a DHCP RESPONSE;transmitting the modified CM configuration filename from the cable modem to the TFTP server ; parsing the modified CM configuration filename into the un-modified CM configuration filename ;generating a second authentication key ;transmitting the CM configuration file to the cable modem only if the first authentication key matches the second authentication key ;wherein the first authentication key and the second authentication key depend upon the un- modified CM configuration filename, the cable modem IP address and the coordination pass phrase.

10/69,K/4 (Item 4 from file: 350)

DIALOG(R) File 350:Derwent WPIX

(c) 2007 The Thomson Corporation. All rts. reserv.

0014763117 - Drawing available

WPI ACC NO: 2005-110771/200512

XRPX Acc No: N2005-095681

Cable modem **transmission restriction method for use with e.g. personal computer, involves transmitting configuration file to cable modem only if authentication keys generated based on configuration file match with each other**

Patent Assignee: DANFORTH A (DANF-I); GOULD K (GOUL-I); TIME WARNER CABLE INC (TIME-N)

Inventor: DANFORTH A; GOULD K

Patent Family (2 patents, 2 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update
US 20050005154	A1	20050106	US 2003613659	A	20030703	200512 B
CA 2473326	A1	20060108	CA 2473326	A	20040708	200612 NCE

Priority Applications (no., kind, date): CA 2473326 A 20040708; US 2003613659 A 20030703

Patent Details

Number	Kind	Lan	Pg	Dwg	Filing Notes
US 20050005154	A1	EN	22	9	
CA 2473326	A1	EN			

Alerting Abstract US A1

NOVELTY - An unmodified **cable modem (CM) configuration filename** is associated to a CM internet protocol (IP) address and an authentication key is generated. A modified **CM configuration filename** is generated by combining previous filename with the key. The modified filename is parsed to unmodified filename by which a new authentication key is generated. The **configuration file** is transmitted to CM only when the keys match mutually.

USE - For providing restricted transmission of **cable modem (CM) configuration file** maintained on trivial file transfer protocol (TFTP) server, for use with terminal such as personal computer and game console device.

ADVANTAGE - Unauthorized access to CM **configuration files** is reduced or eliminated.

DESCRIPTION OF DRAWINGS - The figure illustrates CM request and response for establishing IP connectivity.

Technology Focus

INDUSTRIAL STANDARDS - The authentication key is generated by encryption functions specified by data encryption standard (DES), data encryption algorithm (DEA), extended data encryption standard (DESX), advanced encryption standard (AES) including Rivest's Cipher (RC6), digital signature algorithm (DSA), RC2, RC4, RC5, secure hash algorithm (SHA), message digest algorithm (MD2,MD4,MD5), international data encryption algorithm (IDEA), secure and fast encryption routine (SAFER), fast data encipherment algorithm (FEAL), Skipjack, Blowfish, Carlisle Adams and Stafford Travares (CAST) and ElGamal. The encrypted wireless network conforms to ~IEEE 802.11~ .

Title Terms/Index Terms/Additional Words: CABLE; MODEM; TRANSMISSION; RESTRICT; METHOD; PERSON; COMPUTER; TRANSMIT; CONFIGURATION; FILE; AUTHENTICITY; KEY; GENERATE; BASED; MATCH

Class Codes

International Classification (Main): H04L-009/00

International Classification (+ Attributes)

IPC + Level Value Position Status Version

H04L-0009/32 A I F 20060101

US Classification, Issued: 713200000

File Segment: EPI;

DWPI Class: T01; W01

Manual Codes (EPI/S-X): T01-C03A; T01-D01; T01-F05B2; W01-A05A

Cable modem transmission restriction method for use with e.g. personal computer, involves transmitting configuration file to cable modem only if authentication keys generated based on configuration file match with each other

Original Titles:

Method to block unauthorized access to TFTP server configuration files

Alerting Abstract ...NOVELTY - An unmodified cable modem (CM) configuration filename is associated to a CM internet protocol (IP) address and an authentication key is generated. A modified CM configuration filename is generated by combining previous filename with the key. The modified filename is parsed to unmodified filename by which a new authentication key is generated. The configuration file is transmitted to CM only when the keys match mutually. USE - For providing restricted transmission of cable modem (CM) configuration file maintained on trivial file transfer protocol (TFTP) server, for use with terminal such as personal...
...ADVANTAGE - Unauthorized access to CM configuration files is reduced or eliminated..

Original Publication Data by Authority

Original Abstracts:

The present invention teaches methods and systems for blocking unauthorized access to cable modem configuration files stored on trivial file transfer protocol (TFTP) servers. Filenames are modified by the DHCP to incorporate an authentication key (and optional cloaking) prior to transmission to the cable modem. When the TFTP server receives a modified filename, it also generates an authentication key. The authentication keys must match in order for the cable modem to receive the configuration file requested. At a minimum, authentication keys depend upon the un-modified filename, the cable modem IP address and a "coordination pass phrase" known to the TFTP server and DHCP server, but not known to the cable modem. Variations include optional cloaking, various actions performed for non-matching authentication keys, selection of authentication key generating algorithm and inclusion of cable modem MAC address in the authentication key for all cable modems or for premium service customer cable modems. >

Claims:

What is claimed is: 1. A method for providing restricted transmissions of cable modem (CM) configuration files maintained on a trivial file transfer protocol server (TFTP), the method comprising: using a dynamic host configuration protocol (DHCP) server to associate an un-modified CM configuration filename to a cable modem Internet protocol (IP) address upon receipt of a DHCP REQUEST;

storing a coordination pass phrase on a DHCP server and a TFTP server;generating a first authentication key ;creating a modified CM configuration filename by combining a CM configuration filename with the authentication key ;transmitting the modified CM configuration filename to the cable modem in a DHCP RESPONSE;transmitting the modified CM configuration filename from the cable modem to the TFTP server ; parsing the modified CM configuration filename into the un-modified CM configuration filename ;generating a second authentication key ;transmitting the CM configuration file to the cable modem only if the first authentication key matches the second authentication key ;wherein the first authentication key and the second authentication key depend upon the un- modified CM configuration filename, the cable modem IP address and the coordination pass phrase.

Set	Items	Description
S1	806213	((CABLE OR DATA)()MODEM? OR CABLE? OR COMMUNICATION? OR DATA OR HIGH???()SPEED? OR BROADBAND OR HOOK()UP)(3N)(MODEM? OR DEVICE? OR INSTRUMENT? OR MECHANISM? OR MACHINE? ? OR UNIT? OR APPARAT? OR HARDWARE?)
S2	55564	(KEY? ? OR DEVICE OR MECHANISM?? OR PASSWORD?? OR CODE? ? - OR CODING OR ACCESS?)(5N)(CERTIF? OR AUTHENTIC? OR VERIF? OR - VALID? OR AUTHORI?)
S3	8095	S2(3N)(ONE OR FIRST? OR 1ST OR PRIMARY OR INITIAL? OR ORIGINAL? OR MAIN OR REFER? OR SOURC?)
S4	2438	S3(5N)(MATCH? OR EQUATE? OR EQUATING OR PAIR OR COORDINAT? OR CORRESPOND? OR IDENT? OR SQUARE? OR MATE? ? OR CORRELAT? OR SAME OR MUTUAL? OR DEPEND? OR BASE? ? OR DERIV?)
S5	6677	S2(3N)(SECOND? OR COUPLE OR 2ND OR 2 OR TWICE OR ANOTHER? - OR TWO OR DIFFERENT OR PAIR OR MORE(2N)ONE OR ADDITIONAL)
S6	165885	((SET OR SETT??? OR SETS)()UP OR UPS) OR PARAMETER? ? OR - SETTING? ? OR CONFIGUR? OR PROPERT? OR OPTION? OR PROFIL? OR - PREFEREN?)(3N)(FILE? OR DATA OR INFORMATION OR INFO)
S7	28771	S6(5N)(DELIVER? OR SEND??? OR SENT OR UPLOAD? OR DISTRIBUT? OR TRANSFER? OR TRANSMI? OR BEAM??? OR LOAD??? OR POST??? ?)
S8	36717	S6(5N)(RECEIV? OR ACCEP? OR ACQUIR? OR OBTAIN? OR PULL???-()DOWN?? OR PROCUR??? OR GET? ? OR FETCH??? OR RETRIEV? OR ACCESS?)
S9	10602	S1(2N)(IPADDRESS? OR (INTERNET()PROTOCOL OR IP OR LOGICAL - OR DOT OR NETWORK?)()ADDRESS? OR ADDRESS?)
S10	9	S3:S4 AND S5 AND S1 AND S6 AND S9

File 350:Derwent WPIX 1963-2007/UD=200752
(c) 2007 The Thomson Corporation

File 347:JAPIO Dec 1976-2007/Mar(Updated 070809)
(c) 2007 JPO & JAPIO

Set	Items	Description
S1	306100	((CABLE OR DATA)()MODEM? OR CABLE? OR COMMUNICATION? OR DATA OR HIGH???())SPEED? OR BROADBAND OR HOOK()UP)(3N)(MODEM? OR DEVICE? OR INSTRUMENT? OR MECHANISM? OR MACHINE? ? OR UNIT? OR APPARAT? OR HARDWARE?)
S2	73739	(KEY? ? OR DEVICE OR MECHANISM?? OR PASSWORD?? OR CODE? ? - OR CODING OR ACCESS?) (5N) (CERTIF? OR AUTHENTIC? OR VERIF? OR - VALID? OR AUTHORI?)
S3	3468	S2(3N) (ONE OR FIRST? OR 1ST OR PRIMARY OR INITIAL? OR ORIGINAL? OR MAIN OR REFER? OR SOURC?)
S4	504	S3(5N) (MATCH? OR EQUATE? OR EQUATING OR PAIR OR COORDINAT? OR CORRESPOND? OR IDENT? OR SQUARE? OR MATE? ? OR CORRELAT? OR SAME OR MUTUAL? OR DEPEND? OR BASE? ? OR DERIV?)
S5	3913	S2(3N) (SECOND? OR COUPLE OR 2ND OR 2 OR TWICE OR ANOTHER? - OR TWO OR DIFFERENT OR PAIR OR MORE(2N)ONE OR ADDITIONAL)
S6	261284	((SET OR SETT??? OR SETS)() (UP OR UPS) OR PARAMETER? ? OR - SETTING? ? OR CONFIGUR? OR PROPERT? OR OPTION? OR PROFIL? OR - PREFEREN?) (3N) (FILE? OR DATA OR INFORMATION OR INFO)
S7	14698	S6(5N) (DELIVER? OR SEND??? OR SENT OR UPLOAD? OR DISTRIBUT? OR TRANSFER? OR TRANSMI? OR BEAM??? OR LOAD??? OR POST??? ?)
S8	19978	S6(5N) (RECEIV? OR ACCEPT? OR ACQUIR? OR OBTAIN? OR PULL???-()DOWN?? OR PROCUR??? OR GET? ? OR FETCH??? OR RETRIEV? OR ACCESS?)
S9	581	S1(2N) (IPADDRESS? OR (INTERNET()PROTOCOL OR IP OR LOGICAL - OR DOT OR NETWORK?)()ADDRESS? OR ADDRESS?)
S10	0	S3:S4 AND S5 AND S1 AND S6 AND S9
File	2:INSPEC	1898-2007/Aug W1 (c) 2007 Institution of Electrical Engineers
File	6:NTIS	1964-2007/Aug W3 (c) 2007 NTIS, Intl Cpyrght All Rights Res
File	8:EI	Compendex(R) 1884-2007/Aug W1 (c) 2007 Elsevier Eng. Info. Inc.
File	34:SciSearch	(R) Cited Ref Sci 1990-2007/Aug W3 (c) 2007 The Thomson Corp
File	35:Dissertation	Abs Online 1861-2007/Jul (c) 2007 ProQuest Info&Learning
File	56:Computer and	Information Systems Abstracts 1966-2007/Aug (c) 2007 CSA.
File	60:ANTE: Abstracts	in New Tech & Engineer 1966-2007/Jul (c) 2007 CSA.
File	62:SPIN(R)	1975-2007/Jul W5 (c) 2007 American Institute of Physics
File	65:Inside	Conferences 1993-2007/Aug 15 (c) 2007 BLDSC all rts. reserv.
File	95:TEME-Technology	& Management 1989-2007/Aug W2 (c) 2007 FIZ TECHNIK
File	99:Wilson Appl.	Sci & Tech Abs 1983-2007/Jul (c) 2007 The HW Wilson Co.
File	111:TGG Natl.	Newspaper Index(SM) 1979-2007/Aug 08 (c) 2007 The Gale Group
File	144:Pascal	1973-2007/Jul W5 (c) 2007 INIST/CNRS
File	239:Mathsci	1940-2007/Sep (c) 2007 American Mathematical Society
File	256:TecInfoSource	82-2007/Nov (c) 2007 Info.Sources Inc
File	434:SciSearch	(R) Cited Ref Sci 1974-1989/Dec (c) 2006 The Thomson Corp
File	583:Gale Group	Globalbase(TM) 1986-2002/Dec 13 (c) 2002 The Gale Group